

Technical Features

V64

STANDARD FEATURES

- PRESSURE OPERATED
- KEY SWITCH CONTROL ON BOTH LANDING AND CARRIAGE CONTROLS INCLUDING REMOVABLE KEYS
- EMERGENCY STOP BUTTON
- EMERGENCY MANUAL LOWERING DEVICE
- PROGRESSIVELY MECHANICAL SAFETY GEAR
- SPEED LIMITER
- AUTOMATIC SAFETY EDGES
- HANDRAIL
- ELECTRONIC SAFETY LIMIT SWITCHES
- SHOCK-ABSORBTION DEVICE, ANTI-SHEARING DEVICE ANTI-CRUSHING DEVICES
- WIRELESS CONTROLS

OPTIONALS

- PROTECTIVE COVER (LARGE FOR OUTDOOR, SMALL FOR INDOOR)
- AUTOMATED PLATFORM FOLDING
- SPECIAL SIZE PLATFORM
- AUDIBLE “LIFT IN MOTION” ALARM
- VISUAL “LIFT IN MOTION” ALARM
- FOLDING SEAT
- WIRELESS CONTROLS FOR THE ACCOMPANYING PERSON
- RETRACTING ARMS
- REMOTE CONTROL POST

V64 WITH AUTOMATED PLATFORM FOLDING



TECHNICAL DATA

V64		STANDARD	LARGE	EXTRALARGE
A	MINIMUM STAIR WIDTH	970 mm	1040 mm	1070 mm
B	TOLERATED GRADIENT	FROM 7° TO 50°	FROM 7° TO 50°	FROM 7° TO 50°
C	MINIMUM SIZE OF RAIL	100 mm	100 mm	100 mm
D	MINIMUM SIZE WITH FOLDED PLATFORM	370 mm	370 mm	370 mm
E	PLATFORM DIMENSIONS	830x700 mm	1050x770 mm	1250x800 mm
F	CAPACITY UP TO 45°	300 kg	300 kg	250 kg
G	CAPACITY BEYOND 45°	200 kg	200 kg	200 kg
H	SPEED	5 m/min.	5 m/min.	5 m/min.
I	POWER SUPPLY	230 V	230 V	230 V
J	POWER CONSUMPTION	0,75 kW	0,75 kW	0,75 kW

V64 AND V65 IS REALIZED IN COMPLIANCE WITH ALL AUSTRALIAN STANDARDS AND INTERNATIONAL BEST PREACTICES
THIS DATA ARE INDICATIVE AND NOT BINDING, OUR SUPPLIER RESERVES THE RIGHT TO CHANGE THE SPECIFICATIONS WITHOUT PRIOR NOTIFICATION.

Technical Features

V65

STANDARD FEATURES

- CONTROLS PROTECTED AGAINST UNINTENTIONAL USE, CONSTANT PRESSURE OPERATED
- REMOVABLE KEY
- EMERGENCY STOP
- MANUAL EMERGENCY MANOEUVRE
- PROGRESSIVELY MECHANICAL SAFETY GEAR
- SPEED LIMITER
- AUTOMATIC SAFETY EDGES
- SUPPORTING HANDLE
- ELECTRIC SAFETY LIMIT SWITCHES
- SHOCK-ABSORBING, ANTI-SHEARING, ANTI-CRUSHING DEVICES
- BLACKOUT EMERGENCY BATTERY BACK UP

OPTIONALS

- PROTECTIVE COVER (LARGE FOR OUTDOOR, SMALL FORINDOOR)
- AUTOMATED PLATFORM FOLDING
- SPECIAL SIZE PLATFORM
- AUDIBLE “LIFT IN MOTION” ALARM
- VISUAL “LIFT IN MOTION” ALARM
- INTERMEDIATE STOPS
- FOLDING SEAT
- REMOTE CONTROL POST
- RETRACTING BARS THAT FIT INTO THE ACTUAL BODY OF THE MACHINE (EXCLUDING 1250X800 PLATFORM)
- RADIO CONTROLS FOR THE ACCOMPANYING PERSON

V65 WITH FOLDING SEAT



TECHNICAL DATA

V65		STANDARD	LARGE	EXTRALARGE
A	MINIMUM STAIR WIDTH	1130 mm	1250 mm	1320 mm
B	TOLERATED GRADIENT	FROM 7° TO 50°	FROM 7° TO 50°	FROM 7° TO 50°
C	MINIMUM SIZE OF RAIL	160 mm	160 mm	160 mm
D	MINIMUM SIZE WITH FOLDED PLATFORM	430 mm	430 mm	430 mm
E	PLATFORM DIMENSIONS	830x700 mm	1050x770 mm	1250x800 mm
F	CAPACITY UP TO 45°	300 kg	300 kg	250 kg
G	CAPACITY BEYOND 45°	200 kg	200 kg	200 kg
H	SPEED	8 m/min.	8 m/min.	8 m/min.
I	POWER SUPPLY	230 V	230 V	230 V
J	POWER CONSUMPTION	1 kW	1 kW	1 kW